ALGIWALLPUTTY-675

PROTECTIVE WATERPROOF WALL PUTTY AS BASE TO EXPENSIVE PAINTS

DESCRIPTION:

ALGIWALLPUTTY- 675 is a high strength interior grade water resistant white cement based wall putty ideal for internal walls and ceilings. Algiwallputty-675 has excellent levelling property and gives a very smooth finish which is a very ideal base for painting.

ADVANTAGES

ALGIWALL PUTTY-675:

- Highly economical.
- Excellent potlife of more than 1 hour which reduces wastage and also improves quality.
- Algiwallputty-675 does'nt require water curing.
- Works as an additional water proof layer.
- Doesn't peel off like emulsion based wallputty, hence ideal for locations such as walls exposed to rain and for bathroom walls.
- Much easier to mix compared to similar wall putties hence saves labour effort, time and cost.

AREAS OF APPLICATION:

Remove all loose material with emery paper and water. Mix Algiwallputty-675 with 30-35% clean water till paste of uniform consistency is formed. In case of hot weather moisten the wall surface with water. Apply first coat using putty blade. Allow it to set for 1 to 2 hours. Then apply second coat perpendicular to the first and allow the surface to dry and then apply emery paper no 150/220 to get smooth.

COVERAGE:

The coverage of Algiwallputty-675 on smooth normal plastered wall is 8 to 10 Sq. Ft/Kg for double coat. The coverage area, however, will depend upon the quality and flatness of the substrate.

SHELF LIFE:

24 months if stored in a cool and dry weather away from direct sunlight.

PACKING

Algiwallputty-675 is available in 1kg,5 kg,20 kg, 30 kg, 40 kg and 50 kg packs.









An ISO 9001-2008 Certified Company



www.algitechchemicals.in

ALGITECH CHEMICALS

12/1A, Varambally, NH-17, Brahmavar - 576 213 Udupi Dist., Karnataka State. Tel : (0820) 2560385, 2561483, Fax : (0820) 2560285 Mobile : 9900139257, 98452 42085, 9880779350

Email: contact@algitechchemicals.net, algitech@yahoo.com,

NOTE: The Product should be used in accordance with the manufacturer's instructions. The manufacturer will not be held liable for the performance of the product if the same is not used as per the regulations and limitations specified by the manufacturer and also in conditions where the conditions of use are beyond the control of the manufacturer.

(This Product Used For Industrial Use Only)